



# Huntingdonshire Level 2 Strategic Flood Risk Assessment Site Summary

Site CfS:278

## Final Draft Report

Prepared for  
Huntingdonshire District  
Council

Date  
November 2025

## Document Status

|               |                                                                   |
|---------------|-------------------------------------------------------------------|
| Issue date    | 6 November 2025                                                   |
| Issued to     | Frances Schulz                                                    |
| BIM reference | JFI-JBA-XX-XX-RP-EN-0023                                          |
| Revision      | P03                                                               |
| Prepared by   | Mike Williamson BSc MSc CGeog FRGS EADA<br>Principal Analyst      |
| Reviewed by   | Laura Thompson BSc FRGS<br>Analyst                                |
| Authorised by | Paul Eccleston BA CertWEM CEnv MCIWEM C.WEM<br>Technical Director |

---

## Carbon Footprint

The format of this report is optimised for reading digitally in pdf format. Paper consumption produces substantial carbon emissions and other environmental impacts through the extraction, production and transportation of paper. Printing also generates emissions and impacts from the manufacture of printers and inks and from the energy used to power a printer. Please consider the environment before printing.

---

## Accessibility

JBA aims to align with [governmental guidelines on accessible documents](#) and [WGAG 2.2](#) AA standards, so that most people can read this document without having to employ special adaptation measures. This document is also optimised for use with assistive technology, such as screen reading software.

# Contract

|                     |                                                                 |
|---------------------|-----------------------------------------------------------------|
| JBA Project Manager | Mike Williamson                                                 |
| Address             | Phoenix House, Lakeside Drive, Centre Park, Warrington, WA1 1RX |
| JBA Project Code    | 2022s1322                                                       |

This report describes work commissioned by Huntingdonshire District Council by an instruction via email dated 21 July 2025. The Client's representative for the contract was Frances Schulz of Huntingdonshire District Council. Mike Williamson of JBA Consulting carried out this work.

## Purpose and Disclaimer

Jeremy Benn Associates Limited ("JBA") has prepared this Report for the sole use of Huntingdonshire District Council in accordance with the Agreement under which our services were performed.

JBA has no liability for any use that is made of this Report except to Huntingdonshire District Council for the purposes for which it was originally commissioned and prepared.

No other warranty, expressed or implied, is made as to the professional advice included in this Report or any other services provided by JBA. This Report cannot be relied upon by any other party without the prior and express written agreement of JBA.

JBA disclaims any undertaking or obligation to advise any person of any change in any matter affecting the Report, which may come or be brought to JBA's attention after the date of the Report.

The methodology adopted and the sources of information used by JBA in providing its services are outlined in this Report. The work described in this Report was undertaken between 21 July 2025 and 6 November 2025 and is based on the conditions encountered and the information available during the said period. The scope of this Report and the services are accordingly factually limited by these circumstances.

The conclusions and recommendations contained in this Report are based upon information provided by others and upon the assumption that all relevant information has been provided by those parties from whom it has been requested and that such information is accurate.

---

## Acknowledgements

We would like to thank the Environment Agency, Cambridgeshire County Council for their assistance with this work.

---

## Copyright

© Jeremy Benn Associates Limited 2025

---

# Contents

|          |                                                                                                                       |           |
|----------|-----------------------------------------------------------------------------------------------------------------------|-----------|
| <b>1</b> | <b>Background</b>                                                                                                     | <b>1</b>  |
| 1.1      | Site CfS:278                                                                                                          | 1         |
| <b>2</b> | <b>Flood risk from rivers and sea</b>                                                                                 | <b>5</b>  |
| 2.1      | Existing risk                                                                                                         | 5         |
| 2.2      | Flood risk management                                                                                                 | 6         |
| 2.3      | Impacts from climate change                                                                                           | 7         |
| 2.4      | Historic flood incidents                                                                                              | 7         |
| 2.5      | Emergency planning                                                                                                    | 7         |
| 2.6      | Observations, mitigation options, site suitability, sequential approach to development management - fluvial and tidal | 8         |
| <b>3</b> | <b>Flood risk from surface water</b>                                                                                  | <b>10</b> |
| 3.1      | Existing risk                                                                                                         | 10        |
| 3.2      | Impacts from climate change                                                                                           | 13        |
| 3.3      | Observations, mitigation options, site suitability, sequential approach to development management - surface water     | 16        |
| <b>4</b> | <b>Cumulative impacts assessment and high risk catchments</b>                                                         | <b>18</b> |
| 4.1      | Level 1 cumulative impacts assessment                                                                                 | 18        |
| <b>5</b> | <b>Groundwater, geology, soils, SuDS suitability</b>                                                                  | <b>19</b> |
| <b>6</b> | <b>Residual risk</b>                                                                                                  | <b>22</b> |
| 6.1      | Flood risk from reservoirs                                                                                            | 22        |
| <b>7</b> | <b>Overall site assessment</b>                                                                                        | <b>23</b> |
| 7.1      | Can part b) of the exception test be passed?                                                                          | 23        |
| 7.2      | Recommendations summary                                                                                               | 23        |
| 7.3      | Site-specific FRA requirements and further work                                                                       | 23        |
| <b>8</b> | <b>Licencing</b>                                                                                                      | <b>24</b> |

## List of Figures

|                                                                                                                                                                              |    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Figure 1-1: Existing site location boundary                                                                                                                                  | 2  |
| Figure 1-2: Aerial photography                                                                                                                                               | 3  |
| Figure 1-3: Topography                                                                                                                                                       | 4  |
| Figure 2-1: Existing risk                                                                                                                                                    | 5  |
| Figure 2-2: Natural Flood Management (NFM) potential mapping                                                                                                                 | 6  |
| Figure 2-3: Potential access and escape route                                                                                                                                | 8  |
| Figure 3-1: Surface water flood extents (NaFRA2 - Risk of Flooding from Surface Water map)                                                                                   | 11 |
| Figure 3-2: High risk event surface water flood depths (Third generation - Risk of Flooding from Surface Water map)                                                          | 12 |
| Figure 3-3: High risk event surface water flood hazard (Third generation - Risk of Flooding from Surface Water map)                                                          | 13 |
| Figure 3-4: Low risk event surface water flood extent, as a proxy for the medium risk event plus climate change (NaFRA2 - Risk of Flooding from Surface Water map)           | 14 |
| Figure 3-5: Low risk event surface water flood depths, as a proxy for the medium risk event plus climate change (Third generation - Risk of Flooding from Surface Water map) | 15 |
| Figure 3-6: Low risk event surface water flood hazard, as a proxy for the medium risk event plus climate change (Third generation - Risk of Flooding from Surface Water map) | 16 |
| Figure 5-1: JBA 5m Groundwater Emergence Map                                                                                                                                 | 19 |
| Figure 5-2: Soils and geology                                                                                                                                                | 21 |

## List of Tables

|                                                                                                          |    |
|----------------------------------------------------------------------------------------------------------|----|
| Table 2-1: Existing flood risk based on percentage area of site at risk                                  | 5  |
| Table 3-1: Existing surface water flood risk based on percentage area at risk using the NaFRA2 RoFSW map | 10 |
| Table 5-1: Groundwater Hazard Classification                                                             | 20 |

# 1 Background

This is a Level 2 Strategic Flood Risk Assessment (SFRA) site screening report for Local Plan Site CfS:278. The content of this report assumes the reader has already consulted the 'HDC Level 1 SFRA' (2024) and read the 'HDC Level 2 SFRA Main Report' (2025) and is therefore familiar with the terminology used in this report.

## 1.1 Site CfS:278

- Location: North of Wintringham Hall, Cambridge Road, St Neots
- Existing site use: mainly agricultural though some residential in the southwest corner
- Existing site use vulnerability: more vulnerable
- Proposed site use: commercial
- Proposed site use vulnerability: less vulnerable
- Site area (ha): 18.31
- Watercourse: unnamed ordinary watercourse
- Environment Agency (EA) model: N/A
- Summary of requirements from Level 2 SFRA scoping stage:
  - Assessment of surface water flood extent, depths and hazards
  - Assessment of all other sources of flood risk




Figure 1-1: Existing site location boundary



Figure 1-2: Aerial photography




Figure 1-3: Topography

## 2 Flood risk from rivers and sea

### 2.1 Existing risk

#### 2.1.1 Flood Map for Planning and functional floodplain

Based on the EA's Flood Map for Planning (accessed July 2025) and Flood Zone 3b (functional floodplain), as updated in this Level 2 SFRA, the percentage areas of the site within each flood zone are stated in Table 2-1 and can be viewed on Figure 2-1. This version of the Flood Map for Planning does not consider flood defence infrastructure (Section 2.2) or the impacts of climate change (Section 2.3).

The site is wholly within Flood Zone 1 and therefore at low risk from river and sea flooding. The flood zones to the southeast are likely based on the EA's New National Model.

Table 2-1: Existing flood risk based on percentage area of site at risk

| Flood Zone 1 (% area) | Flood Zone 2 (% area) | Flood Zone 3a (% area) | Flood Zone 3b (% area) |
|-----------------------|-----------------------|------------------------|------------------------|
| 100                   | 0                     | 0                      | 0                      |




Figure 2-1: Existing risk

## 2.2 Flood risk management

### 2.2.1 Flood defences

There are no flood defences in the vicinity of the site, according to the EA's Spatial Flood Defences dataset.

### 2.2.2 Working with Natural Processes

The EA's Working with Natural Processes (WwNP) dataset has been interrogated to identify opportunities for Natural Flood Management (NFM) to reduce flood risk to the site and surrounding areas. These areas are shown in Figure 2-2. Note, the WwNP mapping is broadscale and indicative, therefore further investigation will be required for any land shown to have potential for WwNP.

There may be potential flood risk alleviation to the whole site and wider area through woodland planting and also along the ordinary watercourses through riparian tree planting.




Figure 2-2: Natural Flood Management (NFM) potential mapping

## **2.3 Impacts from climate change**

### **2.3.1 Fluvial**

The EA's Flood Map for Planning shows the site is not at risk from fluvial climate change.

### **2.3.2 Tidal**

The EA's Flood Map for Planning shows the site is not at risk from tidal climate change.

## **2.4 Historic flood incidents**

The EA's Historic Flood Map (HFM) and Recorded Flood Outlines (RFO) datasets have been considered. No historic events have been recorded on or near the site, according to these datasets.

## **2.5 Emergency planning**

### **2.5.1 Flood warning**

The EA operates a Flood Warning Service for properties located within a Flood Warning Area (FWA) for when a flood event is expected to occur. This site is not within a FWA.

Flood alerts may be issued before a flood warning for properties located within a Flood Alert Area (FAA) to provide advance notice of the possibility of flooding. A flood alert may be issued when there is less confidence that flooding will occur in a FWA. The site is not within a FAA.

### **2.5.2 Access and escape routes**

Based on available information, safe access and escape routes could likely be achieved during a flood event via Cambridge Road on the southern boundary, as shown by the orange circle in Figure 2-3.



Figure 2-3: Potential access and escape route

## 2.6 Observations, mitigation options, site suitability, sequential approach to development management - fluvial and tidal

- Observations:
  - The whole site is in Flood Zone 1 and therefore at low risk. The site is also not at any additional risk from climate change.
  - There is no detailed model available for the ordinary watercourse running northwards through the site. Using the 0.1% AEP surface water event as a proxy, risk is modelled to remain confined to the channel.
- Mitigation:
  - Risk from the ordinary watercourse should be confirmed in the site-specific FRA. Modelling may be required to fully understand the onsite fluvial risk.
  - The ordinary watercourse should be included within the site design and layout. Infilling of drainage ditches should be avoided.
  - Given the location of the ordinary watercourse, a flood risk activity permit for development may be required. The type of permission required must be sought from the Environment Agency, Lead Local Flood Authority or Internal Drainage Board. For non-tidal main rivers, a flood risk activity permit may be

required if the development of the site is within 8 metres of a riverbank, flood defence structure or culvert.

- Access and escape:
  - Safe access and escape routes must be available at times of flood and appear to be available via Cambridge Road.

## 3 Flood risk from surface water

### 3.1 Existing risk

The NaFRA2 Risk of Flooding from Surface Water (RoFSW) mapping received a significant update and was published January 2025, including for surface water flood extents and depths. However, at the time of writing, the EA has confirmed that the depth information available is not structured in a way that is suitable for planning purposes. Therefore, this Level 2 SFRA considers the third generation RoFSW depth and hazard mapping in addition to the NaFRA2 extents, as agreed with the EA. Surface water depth and hazard should be modelled at the site-specific FRA stage.

#### 3.1.1 Risk of Flooding from Surface Water - NaFRA2 extents

Based on the EA's national scale RoFSW map, as updated in January 2025, the majority of the site is at very low risk but for several sporadic minor flow paths and areas of ponding.

Table 3-1: Existing surface water flood risk based on percentage area at risk using the NaFRA2 RoFSW map

| Very low risk (% area) | Low risk (% area) | Medium risk (% area) | High risk (% area) |
|------------------------|-------------------|----------------------|--------------------|
| 95                     | 2                 | 1                    | 2                  |




Figure 3-1: Surface water flood extents (NaFRA2 - Risk of Flooding from Surface Water map)

### 3.1.2 Risk of Flooding from Surface Water - third generation depths and hazard

Based on the EA's national scale third generation RoFSW map, there are less areas at risk. The pond in the centre of the site is in both datasets and is mainly shallow and low to moderate hazard.



Figure 3-2: High risk event surface water flood depths (Third generation - Risk of Flooding from Surface Water map)




Figure 3-3: High risk event surface water flood hazard<sup>1</sup> (Third generation - Risk of Flooding from Surface Water map)

### 3.2 Impacts from climate change

The NaFRA2 RoFSW mapping now includes one modelled climate change scenario, the 2050s central allowance for the high, medium and low risk events. However, the upper end allowance on peak rainfall for the 2070s should be assessed in SFRAs. Therefore, at the time of writing, the available national surface water climate change mapping is unsuitable for consideration in development planning. This Level 2 SFRA considers the low risk surface water event as a conservative proxy for the medium risk event plus climate change, as agreed with the EA. The impact of climate change on surface water flood risk should be fully accounted for at the site-specific FRA stage.

Based on the information available, surface water flood risk to the site may increase with climate change with several additional minor flow paths present on the site. Proxy depths are mainly shallow and hazards low though the depths and hazards in the flow path along Cambridge Road in the west of the site are significant in parts. The potential access and escape route should still be achievable though investigation and confirmation will be

<sup>1</sup> Based on Section 7.5 Hazard rating. What is the Risk of Flooding from Surface Water map? Report version 2.0. April 2019. Environment Agency

required through the FRA given the risk shown on Cambridge Road to the west and east of the site.




Figure 3-4: Low risk event surface water flood extent, as a proxy for the medium risk event plus climate change (NaFRA2 - Risk of Flooding from Surface Water map)




Figure 3-5: Low risk event surface water flood depths, as a proxy for the medium risk event plus climate change (Third generation - Risk of Flooding from Surface Water map)




Figure 3-6: Low risk event surface water flood hazard, as a proxy for the medium risk event plus climate change (Third generation - Risk of Flooding from Surface Water map)

### 3.3 Observations, mitigation options, site suitability, sequential approach to development management - surface water

- Current risk to the site is predominantly very low, with 94% of the site being at very low surface water flood risk. Surface water risk in the high and medium risk events is confined to two areas of ponding and the ordinary watercourses.
- The effects of climate change on surface water have not been modelled for this SFRA, however the low risk surface water event has been used as a proxy for the medium risk event plus climate change. Risk is shown to increase in extent though not depth and hazard significantly.
- Surface water flood depths, hazards, including for the impact of climate change should be considered further through the site-specific FRA and drainage strategy. Any surface water modelling at the FRA stage should consider flood depths and hazards.
- The drainage strategy must ensure there is no increase in surface water flood risk elsewhere as a result of new development. Greenfield rates will apply, and the developer should follow the National SuDS guidance and any local guidance available from the LLFA.

- Topographic low spots and flow paths should be incorporated into site design and layout.
- Safe access and escape appear to be possible when accounting for climate change though this should be confirmed through the drainage strategy.
- The RoFSW map is not suitable for identifying whether an individual property will flood and is therefore indicative. The RoFSW map is not appropriate to act as the sole evidence for any specific planning or regulatory decision or assessment of risk in relation to flooding at any scale without further supporting studies, modelling, or evidence.

## 4 Cumulative impacts assessment and high risk catchments

### 4.1 Level 1 cumulative impacts assessment

A cumulative impact assessment was completed through the Huntingdonshire Level 1 SFRA (2024), which aimed to identify catchments sensitive to the cumulative impact of new development. This site is located within one catchment, namely, the Abbotsley and Hen Brooks catchment. This catchment is ranked as a high sensitivity catchment. Planning considerations for sites at high sensitivity to the cumulative impacts of development can be found in Appendix G of the Level 1 SFRA. Cumulative impacts of development should also be considered as part of a site-specific FRA.

## 5 Groundwater, geology, soils, SuDS suitability

Risk of groundwater emergence is assessed in this SFRA using JBA's 5m Groundwater Emergence Map. This dataset is recommended for use by the EA in the SFRA Good Practice Guide<sup>2</sup>. Figure 5-1 shows the map covering this site and the surrounding areas. Table 5-1 explains the risk classifications.




Figure 5-1: JBA 5m Groundwater Emergence Map

The site is shown to be at no risk. Infiltration SuDS should therefore be appropriate.

<sup>2</sup> [Strategic flood risk assessment good practice guide. ADEPT. December 2021.](#)

Table 5-1: Groundwater Hazard Classification

| Groundwater head difference (m)*                                                           | Class label                                                                                                                                                                                                                                                                                                                                                    |
|--------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0 to 0.025                                                                                 | Groundwater levels are either at very near (within 0.025m of) the ground surface in the 100-year return period flood event.<br>Within this zone there is a risk of groundwater flooding to both surface and subsurface assets. Groundwater may emerge at significant rates and has the capacity to flow overland and/or pond within any topographic low spots. |
| 0.025 to 0.5                                                                               | Groundwater levels are between 0.025m and 0.5m below the ground surface in the 100-year return period flood event.<br>Within this zone there is a risk of groundwater flooding to surface and subsurface assets. There is the possibility of groundwater emerging at the surface locally.                                                                      |
| 0.5 to 5                                                                                   | Groundwater levels are between 0.5m and 5m below the ground surface in the 100-year return period flood event<br>There is a risk of flooding to subsurface assets, but surface manifestation of groundwater is unlikely.                                                                                                                                       |
| >5                                                                                         | Groundwater levels are at least 5m below the ground surface in the 100-year return period flood event.<br>Flooding from groundwater is not likely.                                                                                                                                                                                                             |
| N/A                                                                                        | No risk.<br>This zone is deemed as having a negligible risk from groundwater flooding due to the nature of the local geological deposits.                                                                                                                                                                                                                      |
| *Difference is defined as ground surface in mAOD minus modelled groundwater table in mAOD. |                                                                                                                                                                                                                                                                                                                                                                |




Figure 5-2: Soils and geology

## 6 Residual risk

Although a site may be afforded some protection from defences and / or drainage infrastructure, there is always a residual risk of flooding from asset failure i.e. breaching / overtopping of flood defences, blockages of culverts or drainage assets.

Based on available information, there is no residual risk to the site.

### 6.1 Flood risk from reservoirs

The EA's Reservoir Flood Maps (RFM) (2021) show where water may go in the unlikely event of a reservoir or dam failure. Figure 6-1 shows the RFM in a 'dry day' and 'wet day' scenario. A 'dry day' scenario assumes that the water level in the reservoir is the same as the spillway level or the underside of the roof for a service reservoir and the watercourses upstream and downstream of the reservoir are at a normal level. A 'wet day' scenario assumes a worst-case scenario where a reservoir releases water held on a 'wet day' when local rivers have already overflowed their banks.

The site is not shown to be at risk from reservoir failure.

## 7 Overall site assessment

### 7.1 Can part b) of the exception test be passed?

This site is not required to pass part b) of the exception test as it is proposed for less vulnerable uses, however it must still be proven that the development can be safe for its lifetime, which is 75 years for commercial development.

### 7.2 Recommendations summary

Based on the evidence presented in the Level 1 SFRA (2024) and this Level 2 SFRA:

- It should be appropriate to develop this site for more vulnerable purposes given it is wholly located within Flood Zone 1 and not shown to be at additional risk from climate change.
- Risk from the ordinary watercourses should be investigated at the FRA stage. Modelling may be required.
- A detailed drainage strategy will be required for any new development, given the large area of the site and the fact the majority of it is currently greenfield.
- Topographic low spots and flow paths, including the ordinary watercourse, should be incorporated into site design and layout. Infilling of drainage ditches should be avoided.
- Wider opportunities for NFM features to reduce flood risk in the wider area through tree planting in the surrounding areas should be explored at the site-specific FRA stage.

### 7.3 Site-specific FRA requirements and further work

At the planning application stage, the following should be considered:

- Risk from the ordinary watercourse should be investigated at the FRA stage. Modelling may be required in consultation with the EA and LLFA, to robustly define existing and future fluvial flood risk to the site.
- Discharge rates should remain at greenfield rates at a minimum and defined through the drainage strategy. The LLFA should be consulted.
- NFM opportunities should be explored.
- The FRA should be carried out in line with the latest versions of the NPPF; FRCC-PPG; EA online guidance; the HDC Local Plan, and national and local SuDS policy and guidelines.
- Throughout the FRA process, consultation should be carried out with, where applicable, the local planning authority; the lead local flood authority; emergency planning officers; the Environment Agency; Anglian Water; the highways authorities; and the emergency services.

## 8 Licencing


To cover all figures within this report:

- Contains Environment Agency information © Environment Agency and/or database right [2025]
- Contains public sector information licensed under the Open Government Licence v3.0. © Crown copyright and database rights [2025]
- HDC Ordnance Survey licence number: 100022322 [2025]
- © 2021 Esri, Maxar, Earthstar Geographics, USDA FSA, USGS, Aerogrid, IGN, IGP, and the GIS User Community

### Our Offices

Bristol  
Coleshill  
Cork  
Doncaster  
Dublin  
Edinburgh  
Exeter  
Glasgow  
Haywards Heath  
Leeds  
Limerick

Newcastle  
Newport  
Peterborough  
Portsmouth  
Saltaire  
Skipton  
Tadcaster  
Thirsk  
Wallingford  
Warrington



### Registered Office

1 Broughton Park  
Old Lane North  
Broughton  
SKIPTON  
North Yorkshire  
BD23 3FD  
United Kingdom

+44(0) 1756 799919  
[info@jbaconsulting.com](mailto:info@jbaconsulting.com)  
[www.jbaconsulting.com](http://www.jbaconsulting.com)

Follow us on  

Jeremy Benn  
Associates Limited  
Registered in  
England  
3246693

JBA Group Ltd is  
certified to  
ISO 9001:2015  
ISO 14001:2015  
ISO 27001:2022  
ISO 45001:2018

